# 2013 Supply & Accessories Catalog





# SOKKIΛ

# 2013 Supply Catalog

Bags & Carrying Cases	.38
Compass & Clinometers	.26
Field Books	.28
Flagging	.29
Hand Tools	.32-33
Levels	
Abney	. 15
Hand	. 14
Markers	.34
Measuring Tapes	
Chaining Pins	.22
Lufkin	.22-24
Sokkia/Eslon	.25
Paint	.35
Planimeters	.20-21
Plumb Bobs	.31
Prisms, Prism Poles, Accessories	
Accessories	.9
Bipods & Tripods	.9
Data Collector Brackets	.9
Prisms	
Prism Poles	.8,10
Specialty Prisms	.7

Reflective Targets	4
Rods Digital Nedo Fiberglass Specialty	12
Safety	
Specialty Poles GPS Range Robotics	11
Stereoscopes	19
Surveying Markers	30
Thermometers	27
Tripods & Accessories Tripods Nedo Tripods Tribrachs & Adapters	17


(SO) indicates special order items.





### **Reflective Sheet Targets**

Easy-to-use reflective targets supplied on adhesive-backed sheets; can be directly affixed to measuring points. RS\*\*T 0.3mm thin, self-adhesive sheets that adhere to almost any surface. RS\*\*N has normal (0.5mm) reticle lines. For alternative needs, rotary targets and a 2-point target are also available.



The RT90C can be mounted on a tribrach with the AP41 adapter or mounted directly to prism pole.

210160170 RT90C 360° Rotating Sheet Target



### Advanced Prism Systems (AP Series) 40mm

726132 726131 726135 210160005 210160013 210160003 210160003 210160009	AP11A Single Tilting Assembly Single tilting mount with AP01 -40mm prism (SC AP32A Triple Tilting Assembly Triple tilting mount with 3 each AP01 -40mm prise AP01 Prism -40mm in polycarbonate can high-precision, coated AP11 Single Tilting Mount Bayonet base, holds AP01 -40m prism (SO) AP32 Triple Tilting Mount Bayonet base with center hold for single prism (SO) AP11T Single Target attaches to AP11 single mount, non-tilting target (SO) AP01S 10mm adapter ring converts -40mm prism to 30mm P.C. (SO) AP30P Sighting Pole (candy cane) attaches to top of AP11, AP32 or SP11 mount	
	210160005	ain a
	726135	210160013
	210160003	· · · · · · · · · · · · · · · · · · ·

### Standard Prism Systems (SP Series) 0/30mm

726648	SP12A Single Tilting Assembly with Target Assembly, single tilting mount,
	0/-30mm with SP01 prism and poly target

- 210160260 KP01 Prism -30mm, standard prism in polycarbonate can
- 210160203 SP12 Single Tilting Mount with poly target, bayonet base, single mount with target, 0/-30mm, for SP01 prism

210160260



### **Standard Prism Systems**

726668	Single Prism 0/30mm Target with Mount
726669	62mm Prism System with Metal Canister





### Prisms

62mm Prism Plastic Canisters are available in two styles and colors:

724801	Prism 62mm Silver Coated Water Sealed
724802	Economy Prism 62mm Silver Coated
724813	Economy Prism 62mm Copper Coated

Prism mounts are made of all metal with a locking screw for tilting the prism.

724803	Single Tilting Mount Transit Base
724806	Tilting Prism Assembly

# prism. 724803

724801

724813

### Rear Locking Standard Prism Systems

This prism assembly allows the user to quickly adjust the tilting target from behind the prism as it is pointing at the instrument to allow accurate sighting. The targets are 6 in. x 9 in. and available in either florescent orange or yellow. The prism can be either mounted in a 0 or -30mm offset position. All come with a protective carry case for the target or complete system.

724809Tilting Prism Mount with 6 in. x 9 in. Target Florescent Orange724810Tilting Prism Mount with 6 in. x 9 in. Target Florescent Yellow

These complete prism systems come with a 62mm copper-coated prism in a sealed canister.

724811 Tilting Prism Assembly with 6 in. x 9 in. Target Florescent Orange724812 Tilting Prism Assembly with 6 in. x 9 in. Target Florescent Yellow



### **Rear Locking Economy Prism Systems**

This prism assembly allows the user to quickly adjust the tilting target from behind the prism as it is pointing to the instrument to allow accurate sighting. The targets are  $5\frac{1}{2}$  in. x 7 in. and are available in either florescent orange or yellow. The prism can be either mounted in a 0 or -30mm offset position. All come with a protective carry case for the complete target or system.

724804Economy Single Tilting Prism Mount with 5½ in. x 7 in. Target Florescent Orange724805Economy Single Tilting Prism Mount with 5½ in. x 7 in. Target Florescent Yellow



The complete prism systems come with a 62mm silver-coated prism in a sealed canister. Both come in a protective carry case.

724807Economy Tilting Prism Assembly with 5½ in. x 7 in. Target Florescent Orange724808Economy Tilting Prism Assembly with 5½ in. x 7 in. Target Florescent Yellow



# SOKKIΛ

### SPECIALTY PRISMS

### Strobe Prism Assembly

62mm Strobe Prism Assembly with a 5½ in. x 7 in. or 6 in. x 9 in. florescent orange target. The prism can be either mounted in a 0 or -30mm offset position. It works perfectly in low light conditions and all the electronics are housed in the prism canister. The battery is a Sanyo CR-1/3N; good for over 20 hours of use. Comes with a protective carry case for the target or complete system.

724100Strobe Prism Assembly with 5½ in. x 7 in. Target724101Strobe Prism Assembly with 6 in. x 9 in. Target

### P2A Series 25.4mm Mini Prism Assembly

- · This prism is precision ground to 5 arc second accuracy.
- All metal high quality construction.
- · Prism is silver coated with a hard epoxy overcoat to protect against moisture and severe climatic conditions.
- 40 minute vial bubble level side-mounted.
- The prism can be either mounted in a 0 or -30mm offset position.
- · High quality laser engraved manufactured from aircraft grade 6061-T6 billet aluminum.
- · All parts are anodized for long lasting durability.
- Brass Pointed Ears works are vertical line target arrows.
- This kit includes Prism Assembly, Mini Plumb Line Bracket, Mini Plumb Bob, and Durable Carrying Case.

726862 P2A Peanut Prism Assembly

### Mini Prisms Systems

This system contains a copper coated 25mm prism, a tilting holder that has either a side-mounted or center vial. The prism can be either mounted in a 0 or -30mm offset position. Kit comes with two adapters, plumb bob holder and padded carrying case with a beltloop.

724861

724861	Mini Prism System with Non-Adjustable Center vial
724862	Mini Prism System with Non-Adjustable Side Vial

### Pin Pole with Sliding 25mm Prism System

This system includes a 25mm silver coated prism, three 60cm length pole sections – in red and white 10cm stripes (total length is 1.8m/5.9 ft.). The prism can be mounted in a 0mm offset position. This kit also comes with a padded carrying case and a plumb bob hook, and cap for prism to use as an offset prism by itself.

724870 Mini Prism System Kit with Pin Pole



724814 90° L-Bar Monitoring Prism







### Compression/Collet Lock Prism Poles

The Sokkia Compression Lock prism pole offers a secure locking system with a polished aluminum pole with a brass lock. The pole is red and white offered in three sizes with an adjustable tip and dual graduations. Also included with each pole is a carrying case.

724206	8.5 ft. Compression Lock Prism Pole – Adjustable Tip (Dual Graduations)
724207	12 ft. Compression Lock Prism Pole – Adjustable Tip (Dual Graduations)
724208	15 ft. Compression Lock Prism Pole – Adjustable Tip (Dual Graduations)



### Sokkia Knob-Lock Prism Poles

The Sokkia knob-lock prism pole is easy to tighten and release with its large adjustable knob. The pole is red and white offered in three sizes with an adjustable tip and dual graduations. Also included with each pole is a carrying case.

724200	8.5 ft. Knob Lock Prism Pole – Adjustable Tip (Dual Graduations)
724201	12 ft. Knob Lock Prism Pole – Adjustable Tip (Dual Graduations)
724202	15 ft. Knob Lock Prism Pole – Adjustable Tip (Dual Graduations)



### Sokkia Quick-Release Prism Poles

The Sokkia Quick-Release handle lock prism pole allows for quick adjustments to prism heights. The pole is red and white offered in three sizes with an adjustable tip and dual graduations. Also included with each pole is a carrying case.

724203	8.5 ft. Quick Release Lever Lock Prism Pole – Adjustable Tip (Dual Graduations)
724204	12 ft. Quick Release Lever Lock Prism Pole – Adjustable Tip (Dual Graduations)
724205	15 ft. Quick Release Lever Lock Prism Pole – Adjustable Tip (Dual Graduations)





1000183-01 4 Screw Pole Mount Bracket for Mesa

727066

808896

808202

80820

808897

808898

808200

### **Pro Series Lever Lock Prism Poles**

- User friendly lever lock mechanism.
- · One hand operation.
- · Precision CNC marked graduations won't fade or rub off.
- · Heavy duty aluminum construction with electrostatic epoxy powder coat finish.
- 40 minute top-adjust vial bubble level.
- · Fine threaded precise tip allows for precision height adjustment.
- Stainless steel tip points, ultra light weight corrosion resistant hybrid design.
- Available in red/white bands.
- Super lightweight.

727066 8.5 ft. Pro Series Aluminum Lever Lock Prism Pole, Dual Graduations

### Pro Series Knob Lock Prism Poles

- User friendly knob lock mechanism.
- · One hand operation.
- Slip resistant molded rubber knob.
- · Precision CNC marked graduations won't fade or rub off.
- Heavy duty aluminum construction with electrostatic epoxy powder coat finish.
- 40 minute top-adjust vial bubble level.
- · Fine threaded precise tip allows for precision height adjustment.
- Stainless steel tip points, ultra light weight corrosion resistant hybrid design.
- Available in red/white bands.
- Super lightweight.

808200	8.5 ft. Pro Series Aluminum Knob Lock Prism Pole, Dual Graduations
808201	12 ft. Pro Series Aluminum Knob Lock Prism Pole, Dual Graduations
808202	15 ft. Pro Series Aluminum Knob Lock Prism Pole, Dual Graduations
808204	3.6m Pro Series Aluminum Knob Lock Prism Pole, Metric

### **Pro Series Bipods & Tripod**

- Original quick snap bipod & tripod assembly with dual push button thumb release for rapid level adjustment.
- Quick Closure Pole Lock Mechanism allows fast attachments.
- · Accepts pole diameters of 0.75 to 1.5 in. [19 38mm].
- · Quickly and effortlessly convert to a tripod by adding an optional 3rd leg.
- Simple few additional twist of lock knob to secure pole to bipod.
- · Wide stance pivot tang to improve stability by distributing center of mass.
- · All metal CNC construction.
- Stainless steel lightweight points included.
- Manufactured from aircraft grade 6061-T6 billet anodized aluminum, stainless steel and brass.

808896 Pro Series Prism Pole Thumb Release Tripod – Red
808897 Pro Series Prism Pole Thumb Release Bipod – Red
808898 Pro Series Mini Prism Pole Thumb Release Bipod – Red
808895 Additional Leg for Pro Series Bipod

### SPECIALTY POLES

### **Robotic Poles**

Robotic Prism Poles for RC-PR3/4 and adapters for making an RC-PR3 pole adapt to the RC-PR4. Poles with the description RC-PR4 also work with the newest RC-PR5 receiver used with the Sokkia SX. The 727069 has a D-shape pole to keep it from twisting and always aligned for use with the RC unit. 72071 is the standard Robotic Prism Pole sold with the RC-PR5/SX system.

- 727069 8.5 ft. Aluminum Prism Pole for RC-PR3 (Dual Grads Feet / Tenths & Metric)
- 727070 12 ft. Aluminum Prism Pole for RC-PR3 (Dual Grads Feet / Tenths & Metric) (SO)
- 727071 8 ft. Aluminum Lever Lock Prism Pole for RC-PR4, Feet
- 727074 8 ft. Carbon Fiber Lever Lock Prism Pole for RC-PR4, Feet
- 727075 8.5 ft. Carbon Fiber Lever Lock Prism Pole for RC-PR4, Meters

### GPS Poles

- 808016 2m GRX1/GRX2 Rover Pole, Carbon Fiber, 2 section
- 808017 Snap Lock GPS Pole, Carbon Fiber
- 808018 2m Snap Lock GPS Rover Rod
- 2m Snap Lock GPS Rover Rod, Aluminum
- 808090 2m GPS Anti-Crush Aluminum Rover Rod, 2 Section Sokkia Green
- 724290 2m Economy GPS Aluminum Rover Rod, 2 Section Sokkia Green with carrying case
- 724291 2m Economy GPS Carbon Fiber Rover Rod, 2 Section with carrying case

### **GPS** Pole Accessories

808047GPS Quick Release Assembly (top and bottom)808048GPS Quick Release Top (antenna mount)808049GPS Quick Release Bottom (pole mount)



### Heavy-Duty Range Poles

Alternating 12 in. color sections, orange and white.

808849	4 ft. Range Pole Section
808848	8 ft. Range Pole 2 Sections with Point
808847	12 ft. Range Pole 3 Sections with Point

### Pole Peg Adjusting Jig

Pole Peg Adjusting Jig

724301

This simple bracket allows you to adjust and calibrate pole vials in your office. The adjusting jig features a simple L-bracket to set the pole point into and a knob adjusting top to center the pole vial prior to adjusting the bubble.



808090



727069

724290

C Screw

727074

Vial Adjustment



### Sokkia SK Level Rods


- Unique patented oval shape permits equal size graduations full-length, prevents rod from rolling and is easier to hold.
- Numerals and graduations are epoxy-protected for maximum wear-resistance and sized for maximum readability.
- · Sections cushioned with glides to prevent wear.
- Linear accuracy exceeds 1 in 4,000.
- · Made from strong, corrosion-proof fiberglass that is lightweight and won't warp or swell.
- · Rods have height measuring gauge on back side except for 807368 or 807349.
- Female threaded hole (5% x 11 in.) on top for mini-prism.

807344	18 ft. SK Rod, 5 sections, ft./10ths
807338	25 ft. SK Rod, 7 sections, ft./in.
807348	25 ft. SK Rod, 7 sections, ft./10ths
807368	25 ft./7m in length, 7 sections, meters/decimeters/1/2 centimeters & ft./10ths/100ths
807349	32 ft. in length, 9 sections, ft./10ths/100ths with attached footplate
807349	32 ft. In length, 9 sections, ft./10ths/100ths with attached footplate

### Nedo<sup>®</sup> Fiberglass Levelling Rods

- Extremely robust design with Anti-Jam® buttons made of brass ensure a long life.
- · High precision scale on front and back.
- · Scale on back allowing for overall height readings.
- Ergonomically designed shape for a better grip.
- Non-conductive under dry conditions.
- · Laser receiver brackets are easily attached.
- Free carrying bag and snap-on rod level included.
- Quality "Made in Germany".
- · Rectangular.

809109	3m Fiberglass Leveling Rod, 3 sections, m/cm/5mm
809102	13 ft. Fiberglass Leveling Rod, 3 sections, ft/10/100
809106	13 ft. Fiberglass Leveling Rod, 3 sections, ft/in/8th
809110	4m Fiberglass Leveling Rod, 3 sections, m/cm/5mm
809103	16 ft. Fiberglass Leveling Rod, 3 sections, ft/10/100
809107	16 ft. Fiberglass Leveling Rod, 3 sections, ft/in/8th
809111	5m Fiberglass Leveling Rod, 3 sections, m/cm/5mm
809104	25 ft. Fiberglass Leveling Rod, 3 sections, ft/10/100
809112	7.6m Fiberglass Leveling Rod, 3 sections, m/cm/5mm



### SDL Digital Level Rods

Sokkia's RAB-Code (RAndom Bidirectional Code) staffs are designed exclusively for use with Sokkia Digital Levels. Staffs are available in Invar, fiberglass and aluminum and in various lengths.

BIS30A New Super Invar RAB-code Staff (SO)
BIS20 2m Invar Staff Set for SDL30 (Two Rods with Case) (SO)
BIS20 3m Invar Staff Set for SDL30 (Two Rods with Case) (SO)
BGS40 4m Barcode Staff with Case
BGS50 5m Barcode Staff with Case
BGS50G3 16 ft. Barcode Staff with Case
BSS30 30cm Steel Barcode Section with Case (SO)
BSS60 60cm Steel Barcode Section with Case (SO)
BAS55 Aluminum Barcode Staff 5m with Case
GS20L Circular Level for BGS Rod, 20"
GS60L Circular Level for BGS Rod, 60"/2mm with Case
Base Plate (Turtle)



809601

210150013

179876543212987654321-9

### SPECIALTY RODS

### **Direct Elevation Rods**

Lightweight aluminum design.

807650	Direct Elevation Rod, ft./10ths, 10 ft.
807651	Direct Elevation Rod, ft./in., (SO)
807652	Direct Reading Rod 3m (SO)
807653	Replacement Tape 10 ft., 10ths (SO)
1001605-01	Rod, 10' Laser Rod 10ths plus cut/fill
1001607-01	Rod, 15' Laser Rod 10ths
1001991-01	Direct Reading Rod 10' 10ths w/ Receiver guide

### Lumiscale Bar Code Rod

Lumiscale is a self-illuminating bar code rod for use with all digital levels in any low light environment. The face of the rod with the graduations is made of an electroluminescent foil and the body of the rod is made of aluminum. Features an illuminated built in circular bubble.

809701 Ne	do LumiScale with Topcon Bar Code (SO)
809702 Ne	do LumiScale with Sokkia Bar Code (SO)
809704 Ne	do LumiScale with Trimble Bar Code (SO)
809703 Ch	arger with Adapter for Car Power Outlet (SO)

### Rod Level

Determines if the level rod is perpendicular. Head is adjustable so that a true level can be maintained.

724190 Rod Level



### **Builder's Mini Rod**

Unfolds to  $6\frac{1}{2}$  ft. or  $9\frac{1}{2}$  ft. Printed graduations on both sides are embedded below the surface and sealed.

 807548
 6½ ft. Mini Rod, ft./10ths/100ths

 807551
 9½ ft. Mini Rod, ft./10ths/100ths

### Sokkia/SK Measuring Poles

- · Exact measurements of up to 26 ft. or 8m can be read on the enclosed, sealed digital readout.
- · Rugged fiberglass construction with excellent tensile strength.
- · Smooth telescoping movement with friction clamps.
- Only 4 ft. 8 in. closed and less than 5 lbs.
- Linear accuracy exceeds 1 in 2,000.

807376Graduated in ft./in./8ths807386Graduated in ft./10ths/100ths807396Graduated in m/dm/cm/mm

807551





809702



804350

804370

804260

(1)

60

### Hand Level – 1x

Fixed eyepiece; internally mounted bubble assembly and adjustable reflector. Six inches in length with durable finish.

8043501x Hand Level with Bubble Inside804908Replacement Case

### Magnifying Hand Level – 2x

Telescoping hand level extends to 7<sup>3</sup>/<sub>4</sub> in. One inch diameter tube is six inches in length. Padded belt-loop case included.

8043702x Magnifying Hand Level804908Replacement Case

### Magnifying Hand Level – 5x

Provides accuracy at greater distances. Objective lens and eyepiece slide for easy focusing. Stadia lines with 1:100 ratio. Length of  $7\frac{1}{2}$  in. Padded belt loop case included.

8042605x Magnifying Stadia Hand Level804907Replacement Case

### Square-Type Hand Level - 1x

Fixed eyepiece; internally mounted bubble assembly and adjustable reflector. 6 in. in length with durable finish.

804520Square-Type Hand Level804912Replacement Case



1-1-

### ABNEY LEVELS

### Magnifying Abney Level with Stadia – 5x

Percent scale in both directions easy-slide focusing motions for objective and eyepiece. 1:100 stadia. Enamel finished  $7\frac{3}{4}$  in. barrel extends to  $8\frac{5}{6}$  in. Measure existing grades with the 1 x  $3\frac{3}{4}$  in. flat base. Padded belt-loopcase included.

804755Magnifying Abney Level with Stadia804911Replacement Case



### Abney Level with Clinometer

Tube is 5<sup>1</sup>/<sub>8</sub> in. long. Radius arc of 1<sup>1</sup>/<sub>8</sub> in. graduated in degrees (0-90°) in both directions; vernier reading of 10 minutes. Slope scale 1:1 and 1:10. Padded belt-loop case included.

804710 5" Arc, Degree and Slope Abney Level804715 5" Arc, Percent and Degree Abney Level804905 Replacement Case



### **Topographic Abney Level**

Two interchangeable arcs offer chainage correction, degrees  $(0-60^\circ)$  in both directions and percent of grade. Index has friction movement for fine adjustment. Non-glare 6<sup>3</sup>/<sub>6</sub> in. aluminum level tube extends to 7<sup>3</sup>/<sub>6</sub> in. Padded belt-loop case included.

8047456% in. Top with Two Arcs Abney Level804910Replacement Case



### **Double Right Angle Prism**

Two prisms allow for sight to the right and left and clear optical glass for viewing straight ahead. Metal construction. Includes leather case.

724780 Double Right Angle Prism



# **SOKKI**Λ

724645

724675

724281

724252

751250

724445

724251

751252

Builde	r's Series	Tripods		
ltem No.	Min. Height	Max. Height	Height Closed	Type of Head
724445	Aluminum Tripod	Light Weight Quic	k Clamp, Green, F	Flat Head
	34 in.	63 in.	30 in.	% x 11
724645	Aluminum Tripod	Medium Weight C	uick Clamp, Gree	n, Flat Head
	38 in.	63 in.	42 in.	% x 11
724675	Aluminum Tripod	Medium Weight T	wist Lock, Green,	Flat Head
	38 in.	63 in.	42 in.	% x 11
724251	Fiberglass Tripod	with Dual Clamp,	Flat Head	
	42 in.	70 in.	45 in.	% x 11
724252	Wood Tripod Dua	I Clamp with Tool	Kit	
	42 in.	70 in.	45 in.	% x 11
724281	Wood Fiberglass	Tripod Twist Lock		
	42 in.	70 in.	45 in.	% x 11
724282	Wood Fiberglass	Tripod Quick Clar	np	
	42 in.	70 in.	45 in.	% x 11
724647	Domed Medium V	Neight Aluminum	Tripod	
	38 in.	63 in.	42 in.	5∕‰ x 11
724676	Aluminum Tripod	Medium Weight T	wist Lock (Black)	
	38 in.	63 in.	42 in.	% x 11

### **Tripod Stabilizer**

Designed to provide stability when working indoors on concrete and other hard surfaces. Made of heavy-duty aluminum and collapses for compact storage. Comes with rubber O-rings that fit over the feet of the tripod for extra security. 808903 Tripod Stabilizer

### **Professional Series Tripods**

Sokkia Wide-Frame Wood Tripods

All North American maple with metal hardware (no plastic). The hinges are self-adjusting and it has durable nylon bushings for smooth operation. Tripod shoes have large spurs; hardened steel replaceable tips. Bright yellow or Sokkia green finish. Carrying handle.

ltem No.	Color	Height Open	Height Closed	Type of Head	Weight
751250	Green	72 in.	45 ¾ in.	% x 11 flat	14 ½ lbs.
751252	Yellow	72 in.	45 ¾ in.	% x 11 flat	14 ½ lbs.

### Sokkia Wide-Frame Aluminum Tripods

Anodized finish in high-visibility International orange and silver with sling strap for easy hand or shoulder carrying. Extra-long shoes with large spurs for greater anchoring power. Hardened steel, replaceable tripod shoe tips with a screw-style leg or quick release clamp assembly.

Item No.	Height Open	Height Closed	Type of Head	Weight
210150070	PSA1L Aluminu	Im Extension Le	eg Tripod, Quick R	elease Clamp
	67 in.	41 in.	5 x 11 domed	11 ½ lbs.
210150068	PSA1 Aluminur	n Extension Leg	Tripod, Screw Cla	amp
	67 in.	41 in.	5∕‰ x 11 domed	11 ½ lbs.
210150053	PFA1L Aluminu	m Extension Le	g Tripod, Quick Re	elease Clamp
	67 in.	41 in.	5⁄‰ x 11 flat	11 ½ lbs.
210150051	PFA1 Aluminun	n Extension Leg	Tripod, Screw Cla	amp
	67 in.	41 in.	5⁄‰ x 11 flat	11 ½ lbs.



809501

809502

### Nedo<sup>®</sup> Surveyors' Grade Wooden Tripods

- Big round tripod head for easy instrument set-up (approximately 61/2 in. diameter).
- Plastic coated wooden legs ensure a long life.
- Available with Quick Clamp, Screw Clamp or both.
- Brass hinge pins for extra stability.
- · Replaceable points made of hardened steel.
- Snap Cap to protect tripod head.
- · Carrying strap for easy handling.

ltem No.	Min. Height	Max. Height	Height Closed	Weight
59005	TP-5 Surveyors C	Grade Wooden Tri	pod with Quick Cla	amp
	40 in.	66 in.	44 in.	17 lbs.
809502	Surveyors Grade	Wooden Tripod w	ith Screw Clamp	
	40 in.	66 in.	44 in.	17 lbs.
809501	Surveyors Grade	Wooden Tripods	with Dual Clamp	
	40 in.	66 in.	44 in.	17 lbs.

### **Elevating Tripods**

- Robust aluminum top plate with % x 11.
- Double telescope for a large working range.
- · Anodized scale.
- · Robust crank mechanism for easy handling.
- Built-in bubble for easy set-up.
- · Slip-Guard to prevent the legs from spreading unintentionally.
- · Break-proof aluminum quick release levers.

ltem No.	Min. Height	Max. Height	Height Closed	Weight	
809550	Medium Duty Elevating Tripod				
	44 in.	93 in.	48 in.	12 lbs.	
809551	Heavy Duty Elevating Tripod				
	34 in.	112 in.	44 in.	15 lbs.	
60810	Extra Heavy Duty Elevating Tripod				
	33 in.	119 in.	52 in.	19 lbs.	
60811	Giant Elevating Tripod				
	70 in.	157 in.	74 in.	25 lbs.	







### **Precision Tribrachs**

Tribrachs accept Sokkia EDM systems, electronic and optical theodolites, as well as equipment and accessories. Base plate has standard 5% x 11 threads and circular level vial with a sensitivity of 10 min./2mm Push-pull slide focus.

WOA Precision Tribrachs with Optical Plummet (Optical plummet range: 1.5 to 50 ft. [0.5 to 15m]) 210150090 WA201 Precision Tribrach with Optical Plummet

### WAI Precision Tribrachs

221470200 WA200 Tribrach without Optical Plummet (Standard Total Station) 221470300 WA250 Tribrach without Optical Plummet (Motorized Total Station)



724036

210160016

### Laser Tribrach

This tribrach has a bright focused laser dot that provides accurate and quick positioning over a point. It has a push button on/off switch and also maintains the standard 8 minute circular vial. Included is a standard 3 volt CR2 lithium battery. 724034

Tribrach with Laser Plummet, Black 724034

### **Optical Plummet Tribrach**

Tribrach with Optical Plummet, Black 724035

Standard Tribrach

Tribrach without Plummet, Black 724036

### Tribrach Adapters

Adapter accepts all mount and target assemblies; has 60 second level vial for accurate leveling and centering that's adjustable to match height of optical axis above the tribrach. Use with WAI Precision Tribrach: 731134. 210160016 AP41 Tribrach Adapter with Optical Plummet

This adapted shares the same features as 726150, but without the optical plummet. Use with WAI Precision Tribrach: 731135. 210160018 AP44 Tribrach Adapter (SO)

Use this adapter for mounting GPS, prisms and target systems with most tribrachs – has 5/4 x 11 center stud. 724037 **Tribrach Adapter Fixed** 

Adapts GPS, prisms and target systems to most tribrachs - has removable center plug with % x 11 threads and locking screw. Removable center available as a replacement separately. 724038 Tribrach Adapter with removable center





724035

Includes 5% x 11 male thread for attaching GPS, prisms and target systems. Threaded portion attached to rotating plate for easy aiming. Plate has knurled edge and friction stop. 724042 Tribrach Adapter friction rotatable



724042

# SOKKIΛ

### **MS27**

The MS27 offers unmatched precision and ease of use for viewing and interpreting aerial photographs. The distance between the stereo pairs is 27cm, and the field of view is a generous 18 x 23cm. TRA2 tracking device (option) allows for accurate stereoscopic observation over entire overlapped portions of photographs. Illumination unit LA3 is provided as an optional accessory.

MS27 Specifications				
Main Unit				
Distance of optical path	27cm			
Magnification	Swing-in Magnifier: 1.8x BN3 Binocular: 3x, BN8A Binocular: 8x			
Field of view of stereoscope	18 x 23cm			
Field of view of binocular	BN3: 70mm, BN8A: 27mm			
Range of eye-span	55 to 75mm			
Weight	4.0kg (8.8 lbs.)			
PB1 Parallax Measuring Bar				
Minimum graduation / estimation	0.05mm / 0.01mm			
Measurement range	0 to 50mm			
Length / weight	39.5cm / 0.5kg (1.1 lb.)			
TRA2 Tracking Device (option)*				
Size of photographs	Up to 45 x 45cm			
Range of displacement	Latitudinal: 550mm / Longitudinal: 450mm			
*The TRA2 cannot be used with the LA3	Illumination Unit			

\*The TRA2 cannot be used with the LA3 Illumination Unit.

2101531A0 with 210150087

### **MS16**

This small mirror stereoscope is compact yet practical with a 16cm optical path that provides a wide field of view.

MS16 Specifications				
Distance of optical path	16cm			
Magnification	1.5x			
Field of view	10 x 10cm			
Weight	0.7kg (1.5 lbs.)			


210153200 MS16 Small Mirror Stereoscope

### **PS4A & PS2A**

Handy lens-type stereoscopes. Distance between lenses is adjustable from 56mm to 75mm. Two magnifications available, 4x (PS4A) and 2x (PS2A).

210153400PS2A Pocket Stereoscope (2x with Soft Case)210153500PS4A Pocket Stereoscope (4x with Soft Case)





### PLANIMETERS

365161

# SOKKIA

### Planix 5 Planimeter

365161 Planix 5 Electronic Polar Compensator Planimeter



### Planix 7 Roller Planimeter

**Planix 6 Roller Planimeter** 

**Roller Planimeter** 

Planix 6 Electronic Compensator

365170 Planix 7 Electronic Compensator Roller Planimeter

### Planix 10S Digitizing Area Line Meter

365110 Planix 10S Marble Digitizing Area Line Meter



Planimeter Specifications				
	Planix 5	Planix 6	Planix 7	Planix 10S
X, Y Coordinates				
External outputs				
Area	•	•	•	•
Side length				•
Line length				•
Radius				
Center point				
Triangle (base length, height and area)				
Angle (side length and angle)				
Scale: Key input			•	•
Scale: PLOT-real measurement correction				•
Measuring area for differing scale of X,Y			Area Only	Area Only
Sum and average measurement	•	•	•	•
Decimal point set-up				•
Auto power off	•	•	•	•
Calculation				
Display		dot LCD 8 digits x 1 line		dot LCD 16 digits x 2 lines
Measuring range	300mm x 300mm	300mr	n x 3m	300mm x 10m
Minimum line reading		±0.1cm		±0.05mm
Accuracy	±0.2%		±0.1%	
Auto close function				•
Automatic numbering				
Printer				
RS-232C interface cable				

• = option



122110

Lufkin Tap	be Ree	S	
SOKKIA Item No.	Lufkin No.	Length and Width	Graduations
120150	31-100	100'/30m x ¼ or ⁵⁄₁₀ in.	Figure 8, for chain-style tapes
120152-S	31-200	200'/50m x ¼ or ⁵⁄₁₅ in.	D-handle, point, for chain-style tapes
120153 (SO)	31-300	300'/100m x ¼ or 5⁄16 in.	D-handle, point, for chain-style tapes

Lufkin Chain-Style Tapes - Super Hi Way Nubian® (Black) 5⁄16 in.					
Sokkia Item No.	Lufkin No.	Length and Width	Graduations		
122110	O9100B	1201-50, 31-100, 100 ft.	Add feet		
122120	O9200B	1201-52, 31-200, 200 ft.	Add feet		
122130 (SO)	09300B	1201-53 31-300 300 ft	Add feet		

### **Chaining Pins**

724300 14 in. Chaining Pins (Set of 11)

Lufkin Ba	nner Ta	ipes		
Sokkia Item No.	Lufkin No.	Length and Width	Graduations	Color
120315-S (SO)	C216D	100 ft., 3/8 in. wide blade (ring end)	ft./10ths/100ths	Chrome
120325-S	HC256	100 ft.	Inches	Chrome
120335-S (SO)	HW223D	50 ft.	ft./10ths/100ths	n/a
120345-S	HW226D	100 ft.	ft./10ths/100ths	n/a

724300

### Lufkin Architect's Pocket Scale

Yellow-clad ¼ in. x 5 ft. blade with black markings and automatic return. Scales: ¼ and ¼ in. to foot.

120364-S Architect's Pocket Scale Lufkin No.: W393



### **Note on Graduation Styles**

### Add style feet:

Tapes have a blank space at each end. The extra foot before zero is graduated in 10ths and 100ths from right to left. Balance is marked every foot except the last foot of each 100 ft. length, which is in 100ths of feet.

### Add style metric:

Tapes have a blank space at each end. The decimeter before zero is graduated in millimeters from right to left. Balance is marked every decimeter to meter.

# SOKKIΛ

121610

Lufkin Peerless Yellow-Clad Steel Tapes					
Sokkia Item No.	Lufkin No.	Refill Sokkia No.	Refill Lufkin No.	Length and Width	Graduations
121610 (SO)	Y1276	121611	RY1276	100 ft.	ft./in./8ths
121615	Y1276D	121616	RY1276D	100 ft.	ft./10ths/100ths
121620	Y1278	121621	RY1278	200 ft.	ft./in./8ths
121625	Y1278D	121626	RY1278D	200 ft.	ft./10ths/100ths
121630	Y1279	121631	RY1279	300 ft.	ft./in./8ths
121635 (SO)	Y1279D	n/a	RY1279D	300 ft.	ft./10ths/100ths



Lufkin Ny-Clad Steel Tapes					
Sokkia Item No.	Lufkin No.	Refill Sokkia No.	Refill Lufkin No.	Length and Width	Graduations
125253	PS1806	n/a	n/a	100 ft.	ft./inches
125254	PS1806D	n/a	n/a	100 ft.	10ths/100ths
125255	PS1808	n/a	n/a	200 ft.	ft./inches
125256	PS1808	n/a	n/a	200 ft.	ft./10ths/100ths

Lufkin Folding Rules				
Sokkia Item No.	Lufkin No.	Length	Graduations	
120247-S	062CME	6 ft./2m	ft./in./16ths ft. and metric	
120566 (SO)	966	6 ft.	ft./in. and metric	
120575	1066D	6 ft.	ft./10ths/100ths and ft./in./16ths ft., Heavy Duty	
120576	1066DM	6 ft./2m	ft./10ths/100ths/metric, Heavy Duty	

P. C. S



Lufkin Fiberglass Open-Reel Tapes				
Sokkia Item No.	Lufkin No.	Length	Graduations	
125244	1706D	100 ft.	10ths	
125246	1708D	200 ft.	10ths	
125248	1706	100 ft.	inches	
125251	HY1730CME	100 ft./30m	ft./meters	
125252	HV1730DM	100 ft./30m	ft./10ths/100ths	

Lufkin Series 2000 in Chrome-Plated Cases					
Sokkia Item No.	Lufkin No.	Blade Width and Length	Graduations		
120112-S	2312D	¾ in. x 12 ft.	ft./in./16ths ft./10ths/100ths		
120122-S	2325D	¾ in. x 25 ft.	ft./in./16ths ft./10ths/100ths		
120133	2133D	1 in. x 33 ft.	ft./in./16ths ft./10ths/100ths		

120112-S



Lufkin Series HV1000 in Blaze Orange Case			
Sokkia Item No.	Lufkin No.	Blade Width and Length	Graduations
120113-S	HV1048DM	1 in. x 25 ft./7.5m	ft./10ths/100ths/metric
120115-S	HV1048CM	25mm x 8m	metric
120121	HV1425ED	1 in. x 25 ft.	ft./10ths/100ths
120124-S	HY1034DM	¾ in. x 12 ft.	10ths/metric
120128	HV1425D	1 in. x 25 ft.	ft./in./16ths ft./10ths/100ths
120134	HV1312D	¾ in. x 12 ft.	10ths
121915 (SO)	HV1048CME	1 in. x 26 ft./8m	ft./in./8ths/metric
121916	HV1433DM	1 in. x 33 ft./10m	ft./10ths/100ths/metric



120128

### Hammerhead Measuring Tapes with Belt Clips

Available in power tapes, fiberglass tapes or nylon coated steel tapes in many lengths and graduation styles. All cases and reels are sturdy Hi-Visibility green ABS plastic.

Sokkia Item No.	Description	Graduations
870625	1" x 25' Power Tape	in./10ths
1001599-01	1" x 33' with nylon coated blade	in./10ths



### Sokkia/Eslon Fiberglass Utility Tapes (1/4 in. wide)

Especially good for topographic surveys. Extremely light and slip- and tear-proof. (Not supplied with reel.)

845022 Length: 50m, Graduations: 5cm



### Sokkia/Eslon<sup>™</sup> Fiberglass Open-Reel Tapes (½ in. wide)

Lightweight case is virtually shatterproof. The special handle design makes reeling quick. Width ½ in., with folding metal end hook.

Printed on one side. Graduated in ft./in./8ths.

Sokkia Item No.	Length	Refill No.
845142	50 ft.	845162
845144	100 ft.	845164
845146	200 ft.	n/a
845148	300 ft.	n/a

Printed on one side. Graduated in ft./10ths/100ths.

Sokkia Item No.	Length	Refill No.
845242	50 ft.	845262
845244	100 ft.	845264
845245	165 ft.	845265
845246	200 ft.	845266

Printed on one side. Graduated in m/cm/2mm.

Sokkia Item No.	Length	Refill No.
845344	30m	845364
845346	60m	n/a
845348	100m	845368



Printed on both sides.


One side graduated in ft./in./8ths, other side m/cm/2mm.


Sokkia Item No.	Length	Refill No.
845444	100 ft./30m	845464
845445	165 ft./50m	n/a

Printed on both sides.

One side graduated in ft./10ths/100ths, other side m/cm/2mm.

Sokkia Item No.	Length	Refill No.
845542	50 ft./15m	n/a
845544	100 ft./30m	845564
845545	165 ft./50m	845565





### Sokkia/Eslon Warranty

Sokkia/Eslon tapes are covered by a full one-year warranty. If your Sokkia/Eslon tape breaks or if it is defective, Sokkia Corporation will replace it at no charge for up to one full year from the original date of purchase. This warranty also covers defective or broken tape reels and cases. Details are supplied with tapes.

802442

802510

802506

802530

### Suunto Compass/Clinometers

### Compasses

 802430
 51-A-30 Woodsman Compass

 802442
 51-MC-2D Mirror Compass 0-360°



### Sighting

802530	51-KB14/360R Compass 0-360°, Aluminum Case
802535	51-KB14/360RD Compass 0-360° with Adjustable Declination (SO)
802510	51-KB20/360R Compass 0-360°

### Accessories

802503 51-K1335 Rubber Cover, Fits: 802530/802540/802575/802590 (SO)

### **Twin Precision Compasses/Clinometers**

Two instruments in one. Built-in prismatic sighting for fast field use. Resists corrosion, water and impact. Use for directional indications and slope/height measurements with an accuracy of  $\pm 0.25^{\circ}$ .

### 802506 1380 Tandem Compass/Clinometer

### Clinometers

Use as a hand level, builder's level, optical plummet and slope indicator. Measures vertical angles, computes height, determines slope angles and levels for rough surveying. Liquid will not freeze or evaporate.

80257551-PM5/360PC Clinometer80259051-PM5/66PC Height Meter with Slope Scale



### Ushikata Surveying Compass

Handy and compact. A unique "O-BAC" device for one-touch zero setting provides a horizontal reading. Quick magnetic readings with a magnetic induction damper and stadia survey is available with the telescope reticle. Perfect for mountain, forest and range surveying.

S-25 Specifications		
Telescope		reversible, erect, 12x, 120mm long
Horizontal Cir	rcle	5', "O-BAC" zero setting
Compass Cire	cle	Dia. 70mm, 1°
Verticle Circle	9	full circle, 1°
Weight		1.0 kg
802635	Surveving Compass	with Telescope and Case. 0-360° Ushikata Tra

802635 Surveying Compass with Telescope and Case, 0-360° Ushikata Tracon S-2
 802633 Aluminum Extension Tripod with Case (Ushikata Model No. 33)





### THERMOMETERS

### Thermometers

This magnet reset, mercury filled thermometer includes a tenite case.Range -40° to 120° F in 2° increments. Non-refillable.800600Max.-Min. Thermometer

This 5½ in. long thermometer is mercury filled and has a range of -40° to 120° F in 2° increments. Non-refillable. 800610 Pocket Thermometer

The same features as 800610 except with range: 0° to 220° F. Non-refillable. 800620 Pocket Thermometer (SO)

Pocket Thermometer with plastic case that's 5½ in. long. Mercury filled; range: -40° to 120° C in 1° increments. Non-refillable. 800611 Pocket Thermometer–Celsius (SO)

The same features as 800611 but with a refillable metal case.800614Refillable Pocket Thermometer (SO)

Sling Psychrometer that's 6½ in. and mercury filled. Thermometer is recessed and protected by black plastic tube-type case. The outside of the case acts as a handle when operating. White-on-black scale markings; range: 20° to 120° F in 1° increments. 800631 Sling Psychrometer (SO)

Read indoor and outdoor temperatures from inside with bold red and blue numerals. Extend tubing out window to read outdoor temperatures. Range: -45° to 115° F / -40° to 55° C. 800692 Indoor/Outdoor Thermometer (SO)

### **Bi-Therm Thermometers**

As accurate as mercury thermometers, but without the need for safety precautions to avoid potential toxicity. Measures temperature with a bi-metallic coil attached to an indicator needle.



### **Pocket Digital Thermometer**

High precision pocket digital thermometer. Able to be recalibrated. Maximum/minimum temperature feature retains memory even when turned off. Two-stage off button with timer, auto-off feature to conserve battery, replaceable watch battery installed. 4½ in. stainless steel stem. Range: -58° to 500° F / -50° to 260° C.

800690 Pocket Digital Thermometer





### **Field Books**

Left page with blue horizontal lines and red vertical lines. Right page with 4 squares per inch and red vertical line. 815260 Field Book ( $4\frac{1}{2} \times 7\frac{1}{4}$  in.)

Both pages with 10 squares per inch with inch lines slightly heavier. 815275 Cross-Section Book  $(6\frac{1}{2} \times 8\frac{1}{2} \text{ in.})$ 

Both pages with blue horizontal lines and red vertical lines. Six vertical columns per page. 815250 Level Book (4 x 6<sup>1</sup>/<sub>2</sub> in.)

Both pages with blue horizontal lines and red vertical lines. Six vertical columns per page. 815255 Level Book ( $4\frac{1}{2} \times 7\frac{1}{4}$  in.)

### Loose-Leaf Sheets

Single sheets: 50 singles per package, 12 packages per carton, sold by the package. 815350 Level Book ( $4\frac{1}{2} \times 7\frac{1}{4}$  in.)

### **Specialty Field Books**

Left page level ruled. Right page with 8 squares per inch and red vertical center line. 815220 Mining Transit Book ( $4\frac{1}{2} \times 7\frac{1}{4}$  in.)

Left page level ruled. Right page with 10 squares per inch, red vertical center line and heavy inch lines. 815230 Engineer's Field Book (4½ x 7¼ in.)

### Transit/Economy Field Books

Left page level ruled. Right page with 8 vertical and 4 horizontal blue lines and red vertical center line. 815200 Transit Field Book ( $4\frac{1}{2} \times 7\frac{1}{4}$  in.)

### Loose-Leaf Sheets

Single sheets: 50 singles per package, 12 packages per carton, sold by the package. 815300 Transit Field Book  $(4\frac{1}{2} \times 7\frac{1}{4} \text{ in.})$ 

Heavy paper cover, spiral bound and 36 pages. 815205 Economy/Student Field Book

Heavy paper cover, saddle stitched (stapled) and 32 pages. 815210 Economy Field Book

### Rite-In-The-Rain<sup>®</sup> Weatherproof Field Books

80 leaves, ruled 8 vertical lines per inch, covered in yellow poly. Size: 4% x 7 in. 815400 Transit Book #300

80 leaves, ruled 6 vertical columns per page, covered in yellow poly. Size: 4% x 7 in.
815405 Level Book #310

### Loose-Leaf Sheets - 100 loose-leaf packs.

- 815410 Transit Book Sheets #302 (same layout as 815260)
- 815415 Level Book Sheets #312 (same layout as 815250)


### **High-Visibility Buckram Binders**

Buckram-covered stiff board construction-lined with black paper. Six-ring style.81537050-page capacity binder with ½ in. rings. Size: 5½ x 7¾ in.815375100-page capacity binder with ¾ in. rings. Size: 5½ x 7¾ in.


### **High-Visibility Polyethylene Binders**

One-piece, 55-gauge single-piece cover resists dirt and withstands tough weather. Six-ring style.


- 815378 100-page capacity with <sup>3</sup>/<sub>4</sub> in. rings. Size: 5<sup>1</sup>/<sub>2</sub> x 7<sup>3</sup>/<sub>4</sub> in.
- 815379 50-page capacity with  $\frac{1}{2}$  in. rings. Size:  $5\frac{3}{4} \times 7\frac{3}{4}$  in.









815275





815220







# SOKKIΛ

### Presco "Texas" Flagging

Colorfast and rainproof. Contains no toxic lead. Packed one dozen to a box; sold by the box. Size: 1 in. wide. Note: Colors cannot be assorted within the box.

- 8110\_\_
   Solid 300 ft. roll. Specify color with last two digits:

   -00 Red, -01 Orange, -02 Blue, -03 Yellow, -04 White, -06 Black, -11 Green.
- 8112\_\_\_
   Florescent 150 ft. roll. Specify color with last two digits:

   -00 Red Glo, -01 Orange Glo, -03 Yellow Glo, -04 Pink Glo, -06 Lime Glo.

### Presco "Arctic" Flagging

Excellent durability and perfomance at low temperatures. -40° F temperature resistance. Packed one dozen to a box; sold by the box. Size: 3mm for standard colors, 5mm for florescent colors. Note: Colors cannot be assorted within the box.

- 8110\_\_
   Florescent 150 ft. roll. Specify color with last two digits:

   -69 Yellow Glo, -70 Orange Glo, -71 Pink Glo, -72 Blue Glo, -73 Lime Glo.
- 8110\_\_\_\_ Solid 300 ft. roll. Specify color with last two digits: -77 White, -78 Blue.



### Stake Flags

Vinyl flags securely attached to stiff steel wire stakes. Packed 100 to a bundle with 10 bundles per box. Sold by the box. Order in increments of 10.

### Small Flags (21/2 x 31/2 in.)

- 8108\_\_ 21 in. stakes. Specify color with last two digits: -00 Pink Glo, -01 Orange Glo, -03 Yellow, -06 White.
- 8109\_\_ 30 in. stakes. Specify color with last two digits: -00 Pink Glo, -01 Orange Glo, -03 Yellow, -04 Red, -06 White.

### Large Flags (4 x 5 in.)

- 0802\_\_ 21 in. stakes. Specify color with last two digits: -11 Blue, -12 White, -13 Red, -14 Blue Glo, -15 Yellow, -16 Orange Glo, -17 Pink Glo, -18 Yellow Glo, -19 Red Glo, 099992 Orange.
- 0803\_\_ 30 in. stakes. Specify colors with last two digits: -01 Blue, -02 Orange Glo, -03 Red, -04 White, -05 Yellow, -06 Blue Glo, -07 Pink Glo, -08 Lime Glo, -09 Red Glo, -16 Yellow Glo, -24 Orange, 080298 Green, 099071 Green Glo.
- 8113\_\_ 36 in. stakes. Specify colors with last digit: -00 Pink Glo, -01 Orange Glo, -02 Blue, -03 Yellow.

### Aerial Flagging

Sold by the roll.

10164 White Roll, 300 ft. x 12 in.

# 811010


**Flagging Tape Dispenser** Lightweight, rustproof and fits on a belt or waistband. Holds one roll.

811010 Flagging Dispenser

### Stake Whiskers

Packed 25 per bundle. 40 bundles per box.

117\_\_\_\_\_-41 Orange, -50 Red, -51 Blue, -53 Pink Glo, -54 White, -55 Orange Glo.





### **Mag Nails**

Revolutionary new metal formula doubles or quadruples detection by metal detectors by retaining magnetism. Larger center point for easier driving. Packaged in boxes of 100.





### Stake Tacks

Steel, <sup>7</sup>/<sub>8</sub> in. long tacks with indented head to guide plumb bob point. Approximately 725 per 1 lb. box.

813270 Stake Tacks 096000 Tack Ball



### Nail Markers

One-inch squares made of plastic impregnated nylon in florescent orange. Approximately 70 per package.

811501 811502	Nail Markers with ¼ in. hole Nail Markers with ½ in. hole	811501
	•	0

### Lead Wire

For lead and tack reference points. Fits hole cut by No. 813089 Concrete Drill. Diameter: % in., Length: 15 in.

813220 Lead Wire

### **Monument Spikes**

Large monument spike  $\frac{3}{6}$  in. square shank. Galvanized with chisel point and button head. Makes ideal bench mark or turning point.



### Flat Survey Markers

Cast from solid brass. Ribbed shank prevents turning or loosening. Non-glare finish, ½ in. thick top. Shank area 0.4 sq. in., length: 2 in. Units - Each.

813400	1% in. Top Diameter	State of the
813403	2 in. Top Diameter	A TENES
813406	21/2 in. Top Diameter	
813408	3 in. Top Diameter	813406
813408-SF	3 in. Top Diameter Satin Finish	813400

### **Domed Survey Markers**

Solid brass with curved heads. Ribbed shank prevents turning or loosening. Shank area: 0.4 sq. in.; shank length: 2 in. Units - Each.

813410	1% in. Top Diameter
813413	2 in. Top Diameter
813416	2 1/2 in. Top Diameter
813418	3 in. Top Diameter



### Surveyor's Flat Shiners

Tin, 2<sup>1</sup>/<sub>4</sub> in. diameter with center punch and crimped edges. Especially valuable for indicating semi-permanent points with spikes or nails. 3 lb. carton.

813430 Flat





### Surveyor's Raised Shiners

Tin, 1<sup>1</sup>/<sub>4</sub> in. diameter with center punch and crimped edges. Especially valuable for indicating semi-permanent points with spikes or nails. 1 lb. carton.

Approximately 250 per box.

813431 R

Raised Shiners



### Mag Hubs

The Mag Hub is magnetized for easy detection and zinc plated to resist corrosion. It has a large center point and is easy to carry. Not for use in concrete or asphalt. 30 lb. box. ¼ in. diameter.

4 in. M
6 in. M
8 in. M

in. Mag Hub Nail in. Mag Hub Nail in. Mag Hub Nail



### PLUMB BOBS

### Plumb Bobs

Screw caps and hardened steel points with standard threads. Storage space for an extra point inside the cap.

812212	12 oz. Plumb Bob
812214	14 oz. Plumb Bob
812216	16 oz. Plumb Bob
812218	18 oz. Plumb Bob
812224	24 oz. Plumb Bob
812290	Extra Point (fits all listed plumb bobs)
812293	Extra Cap (fits all listed plumb bobs)



### Plumb Bob Cords

Made with the finest quality braided cord.

812413	White Poly; 50 yd. Spool
812423	Orange Poly, 50 yd. Spool
812439	Fluorescent Yellow Poly, 50 yd. Spool
812440	Flourescent Red Poly, 50 yd. Spool

### Leather Scabbards

Rugged leather with stitched and riveted pockets that hold tape or Gammon Reel and a 16 or 18 oz. plumb bob.

812440

879200

812365 Leather Scabbard for Gammon Reel and Plumb Bob

Extra-heavy stitched and riveted pocket.

812350	Belt for Plumb Bob Scabbard
812315	Scabbard for 10–14 oz. Plumb Bobs
812325	Scabbard for 16–18 oz. Plumb Bobs
812335	Scabbard for 24–32 oz. Plumb Bobs

### Tally Register

Four-digit capacity with quick return to zero.

879200 Tally Register

### **Gammon Reels**

Handy, retracting plumb bob cord reel means no more winding and no more broken or muddy string. Includes 72 lb. test nylon string that weighs 1½ oz.

812448	12 ft. Gammon Reel, Black/Orange
812449	12 ft. Gammon Reel, White/Orange
812450	61/2 ft. Gammon Reel, White/Orange
812451	24 yd. Nylon Refill, Red/Orange
812452	24 yd. Nylon Refill, Fluorescent Yellow
812454	24 yd. Nylon Refill, Fluorescent Red

### Targets

Available in "Quik-Stik," plastic and translucent plastic variations.

- 812620 Plastic target notched for attaching to line 2<sup>1</sup>/<sub>2</sub> x 4 in., red/white
- 812625 Translucent Plastic target laminated for brilliant illumination and notched for attaching to line 2<sup>1</sup>/<sub>4</sub> x 4 in., black/orange
- 812640 Quik-Stik target with paper back that peels off instantly and sticks to any surface 2 x 3½ in. (package of 25)








### HAND TOOLS

## SOKKIA





### Difference State S



### **Tool Pouches**

818116	7-Pocket Tool Pouch
818115	Leather Tool Pouch



818116





813501

813050

### Dixon Redimark<sup>®</sup> Marker

Tight-seal, no-roll cap makes marker last longer; stores on base when not in use. -NEW MARK Chisel point is ideal for marking on wood, metal, glass, plastic or paper. Aluminum body gives 30% more volume. Sold by the dozen.

813471 Black Dixon Felt Tip Marker 813472 Red Dixon Felt Tip Marker

### Ideal Mark<sup>®</sup> Marking Pen

Industrial-grade marker for surveying and construction layout. Valve action with indelible black ink. VALVE ASTION INDELIDIT MARK Replaceable tip and metal cap with pocket clip. Sold by the dozen.

- 813501 Black Ideal Mark with Replaceable Bullet Tip, Box of 12
- 813502 Red Ideal Mark with Replaceable Bullet Tip, Box of 12
- 813503 Replacement Tip, Bullet Style (12 tips per package)
- Replacement Tip, Chisel Style (12 tips per package) 813504

### **Carbide Point Scribes and Heavy Duty Scribers**

For marking steel, concrete, stone, lumber and almost any other surface.

813050 Carbide Point Scriber; 51/4 in. 813051 Replacement Scriber Point (6 per package) Premium Scribe: 5 in. 813053 **Giant Scribe** 813054 Replacement Tip for 813053/813054 (6 per package) 813055

### Dixon<sup>®</sup> Lumber Crayons

For marking steel, concrete, stone, lumber and almost any other surface. Length: 41/2 in.; diameter: 1/2 in. Packed 12 per box; sold by the box.

813461	Carbon Black Crayon
813462	Yellow Crayon
813463	Red Crayon
813464	Fluorescent Pink
813465	Blue Crayon
813467	White Crayon



### Dixon<sup>®</sup> Wood Crayon Holder

813468 Wood Crayon Holder





o lears. The Pr

### Aervoe Marking Paint

### **Survey Marking Paint**

- Aervoe's Survey Marking Paint offers the best in color visibility and retention, durability, and a lasting mark of up to six months.
- Non-freezing and operational to 14°F.
- · Colors are formulated to meet standards set by OSHA and APWA/One Call Systems.
- Mark is visible for up to six months depending on traffic and exposure.
- Adheres to many surfaces including wood, concrete, asphalt, brick and gravel.
- Not recommended for use on turf surfaces.
- 17 oz.

813454Flo Orange #222813460Flo Pink #229

### Spray Paint Marking Wand

Lightweight durable steel and plastic construction with a comfortable grip for easy marking.

813958 Marking Wand, 24 in. Handle

### Spray Paint Marking Pistol

Use with marking paints for increased accuracy and no mess. Light touch spray control. Easy loading.

813959 Marking Pistol





813630

SOM

SOKKIA

813640

### Hard Hats

High-density polymer for excellent protection against severe impact. Molded in one piece with no metal; protects against corrosive materials. Meets ANSI Z89. 1-196 (Class A) - Federal Spec GGG-H-142g. Fits sizes 63% through 8. Weight: 11 oz.

813630 Yellow 813631 White

### Surveyor's Umbrella

63 in. spread and 8 ft., 3-section pole with baked aluminum enamel finish.

813640	Heavy-drill fabric umbrella; blue and yellow
813641	Water resistant vinyl umbrella; yellow with blue logo
813642	Replacement Pole for 813640/813641, diameter 1¼ in. (SO)



Sokkia Corporation is now offering a new version of First Aid Kits, sized for various work requirements. The Jobsite kit is designed to serve most minor first aid issues for up to 25 people. The Truck kit is designed for up to 10 people.

First Aid Kit (Truck) 813094 813095 First Aid Kit (Jobsite)



### **Class 2 Safety Vests**

Sokkia's Class 2 safety vests come in high-visibility orange or lime green with mesh or solid materials.

803000	Class 2 Mesh Vest Lime LG 3 Pockets Velcro	2
803001	Class 2 Mesh Vest Orange LG 3 Pockets Velcro	
803002	Class 2 Mesh Vest Lime XL 3 Pockets Velcro	
803003	Class 2 Mesh Vest Orange XL 3 Pockets Velcro	
803004	Class 2 Mesh Zip Lime LG No Pockets	
803005	Class 2 Mesh Zip Orange LG No Pockets	
803006	Class 2 Mesh Zip Lime XL No Pockets	
803007	Class 2 Mesh Zip Orange XL No Pockets	
803008	Class 2 Surveyors Vest Lime LG Zip	
803009	Class 2 Surveyors Vest Orange LG Zip	
803010	Class 2 Surveyors Vest Lime XL Zip	
803011	Class 2 Surveyors Vest Orange XL Zip	Terre and
803012	Class 2 Mesh Snap Front 9 Pocket Orange LG	44
803013	Class 2 Mesh Snap Front 9 Pocket Orange XL	



ite First Aid Kit 25 P

### Important!

Requirements for work area safety vary from state to state. Please consult your local authorities for details.

### Traffic Cones

High-intensity fluorescent red-orange PVC cone with weighted base for stability.

 813612
 12 in. Traffic Cone

 813618
 18 in. Traffic Cone

 813619
 28 in. Traffic Cone



### Non-Reflective "SURVEY CREW" Sign

Non-reflective, high-visibility orange sign with rib support. Roll-up design for daytime use. Stand sold separately.

813652 36 in. SURVEY CREW non-reflective sign

- 813653 48 in. SURVEY CREW non-reflective sign
- 813656 Replacement Rib Set 36 in.
- 813657 Replacement Rib Set 48 in.

### Reflexite "SURVEY CREW" Sign

Reflexite Super Bright<sup>™</sup> orange sign with rib supports. Roll-up design for day and night visibility. Stand sold separately.

- 813654 36 in. SURVEY CREW Reflexite sign (SO)
- 813655 48 in. SURVEY CREW Reflexite sign (SO)
- 813656 Replacement Rib Set 36 in.
- 813657 Replacement Rib Set 48 in.

### **Uniflex Screwlock Sign Stand**

NCHRP-350 approved design. Single heavy-duty coil spring to hold 36 in. and 48 in. signs. Kick-release adjustable legs for easy setup. Stand only. Sign sold separately.

813651 Uniflex Screwlock Sign Stand

### T-50 Economy Tripod Sign Stand

NCHRP-350 approved design with roll-up signs on low speed roadways. Holds 36 in. or 48 in. signs. For day and night visibility. Stand only. Sign sold separately.

813650 T-50 Economy Tripod Sign Stand

Caution Tape Caution tape; yellow; 3 mil, 1,000 ft.


811050 Caution Tape (1 roll)











SOKKIA	N




SOKKIA	NOTES








# **Sokkia Corporation**

16900 W. 118th Terrace • Olathe, KS 66061 800.4.SOKKIA • www.sokkia.com

SOK-1017 Rev A 3/13

Due to the printing process, the colors of the products printed in this catalog may vary slightly from those of actual products. Products displayed within are not to scale. Designs and specifications are subject to change without notice. All weights are approximate. Certain products in this catalog may not be available in specific market areas. Please consult with your nearest Sokkia representative for details. © 2013 Topcon Corporation. All rights reserved. Sokkia is a trademark of Sokkia Topcon Co. Ltd. Other trademarks and trade names are those of their respective owners.